

Firefighter I Written Exam Sample

1. If 24 feet of a 35-foot extension ladder is needed to reach a victim, the butt of the ladder should be placed approximately _____ feet from the building.
A. 4 B. 6 C. 8 D. 11
2. When conducting a primary search within a structure, a firefighter should begin:
A. in the center of the room B. on the wall
C. in a closet D. under or behind furnishings
3. The movement of heat through a steel beam to an unexposed part of the building where it starts another fire is an example of:
A. conduction B. radiation
C. convection D. direct-flame contact
4. Prior to entering a fire area with a charged hoseline, the nozzle operator should first:
A. bleed air from the line B. wait for a building layout
C. wait for the power to be shut off D. determine whether a BLEVE is possible
5. When a fire rekindles and has to be put out a second time, it is usually an indication of poor:
A. salvage B. water pressure
C. overhaul D. ventilation
6. Which of the following **is not** a recommended method of drying a hose that has been washed and cleaned?
A. Hose tower B. Hose drying rack
C. Mechanical hose drier D. Hot pavement
7. Life safety, incident stabilization, and _____ are the three most important organizational duties for fire departments to pursue.
A. building inspections B. public information
C. property conservation D. resource management
8. Fire service rope falls into two use classifications:
A. life safety and utility B. braided and Kernmantle
C. dynamic and static D. natural and synthetic